

ARTICLE INFORMATION SHEET



MATERIAL SAFETY DATA SHEET in accordance with paragraph (g) of OSHA Regulations (Standards - 29 CFR) Hazard Communication. - 1910.1200)

Electra XD Thermal Plate / US/C

1. Chemical Product and Company Identification

Common Name : Electra XD Thermal Plate / US/C **KPG#** P0581
MSDS # 858
Version 1
Validation Date 2008-11-19

Synonym : P0080

Area of Application : Industrial applications. Graphic Arts Imaging.

Supplier : Eastman Kodak Company
343 State Street
Rochester, New York, 14650
USA

Emergency telephone number : In Case of Emergency (medical/roadside) (24hrs) **CALL 1-800-451-8346**

For other EHS Information : Eastman Kodak Company, Graphic Communications Group
Health, Safety & Environment
11465 Johns Creek Parkway, Suite 260, Duluth GA 30097 USA
EnviroServices Hotline: 1-877-574-7274 or 770-232-2133
Email: PEP@kodak.com; Fax: 770-232-2150

2. Composition, Information on Ingredients

Product type	: Article.	
Name	CAS #	% by Weight
Aluminium	7429-90-5	>99
Resins and Colorants	--	<1

There are no other components present which, to the best of our current knowledge and in the concentrations applied, are hazardous to health or environment.

3. Hazards Identification

During imaging low levels of emissions of hazardous substances (thermal by-products) may be produced. However, under normal conditions of use the plate will not pose a physical hazard or health risk to employees.

4. First Aid Measures

Eye Contact : Not applicable.

Ingestion : Not applicable.

Skin Contact : Standard procedure for responding to cuts or lacerations.

Inhalation (of by-products upon heating) : Allow the victim to rest in a well-ventilated area.

5. Fire Fighting Measures

Fire Fighting Media and Instructions

Suitable : Use extinguishing media suitable to primary cause of fire.

Not suitable : None.

Unusual fire/explosion hazards : None.

Continued on Next Page

Hazardous thermal (de)composition products : See section 8.

Protection of fire-fighters : No special protection is required.

6. Accidental Release Measures

Not applicable.

7. Handling and Storage

Personal precautions : None.

Storage : Keep in a cool, well-ventilated place.

For specific information regarding optimal storage conditions, refer to the general instructions for use of this product.

Handling: Potential lacerations from the thin gauge aluminum, while unlikely when handled properly, cuts or lacerations from aluminum should receive proper first aid/medical attention.

8. Exposure Controls, Personal Protection

The laser exposure process used to image this product may produce gases and particulates as thermal decomposition by-products. Trace amounts of hazardous and non-hazardous gases such as the ones listed below may be produced during laser imaging and processing.

Product Name	CAS #	Exposure Limits
Acetaldehyde	75-07-0	ACGIH TLV (United States, 1/2008). CEIL: 45 mg/m ³ OSHA PEL (United States, 11/2006). TWA: 360 mg/m ³ 8 hour/hours.
Acetone	67-64-1	ACGIH TLV (United States, 1/2008). STEL: 1782 mg/m ³ 15 minute/minutes. TWA: 1188 mg/m ³ 8 hour/hours. NIOSH REL (United States, 12/2001). TWA: 590 mg/m ³ 10 hour/hours. OSHA PEL (United States, 11/2006). TWA: 2400 mg/m ³ 8 hour/hours.
2-Butanone (MEK)	78-93-3	ACGIH TLV (United States, 1/2008). STEL: 885 mg/m ³ 15 minute/minutes. TWA: 590 mg/m ³ 8 hour/hours. NIOSH REL (United States, 12/2001). STEL: 885 mg/m ³ 15 minute/minutes. TWA: 590 mg/m ³ 10 hour/hours. OSHA PEL (United States, 11/2006). TWA: 590 mg/m ³ 8 hour/hours.
Formaldehyde	50-00-0	ACGIH TLV (United States, 1/2008). Skin sensitizer CEIL: 0.37 mg/m ³ NIOSH REL (United States, 12/2001). CEIL: 0.1 ppm 15 minute/minutes. TWA: 0.016 ppm 10 hour/hours. OSHA PEL Z2 (United States, 11/2006). STEL: 2 ppm 15 minute/minutes. TWA: 0.75 ppm 8 hour/hours.

Engineering Controls :

It is the user's responsibility to install adequate engineering controls to ensure environmental and safety compliance with all local, state, and federal regulations. The following are general recommendations:

Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Avoid overexposure as this will raise the emission levels.

Respiratory Protective measures : None should be needed.

9. Physical and Chemical Properties

Physical State and Appearance	: Solid. (Plate)	Odor	: Odorless.
pH	: Not applicable.		
Melting/Freezing Point	: >200°C (392°F)		
Density	: 2700 kg/m ³		
Specific Gravity	: Not available.		
Vapor Density	: Not applicable.		
Solubility	: Insoluble in cold water.		

10. Stability and Reactivity

Stability and Reactivity	: The product is stable.
Hazardous Decomposition Products	: See section 8.
Hazardous Polymerization	: Will not occur.

11. Toxicological Information

Not applicable.

12. Ecological Information

This material has not been tested for environmental effects.

13. Disposal Considerations

The imaged and processed plates were tested using the Toxicity Characteristic Leaching Procedure (TCLP) and are not characterized as a hazardous waste for disposal purposes as defined by the US EPA. However, customers should consult the local regulations for disposal requirements. We recommend having waste offset plates being hauled away by a licensed company for aluminum recovery.

If chemical and particulate filters are used, follow the manufacturers recommendations and dispose of them in accordance with all state, local, and federal regulations.

14. Transport Information

Offset plates are not regulated as a hazardous material under domestic or international transport regulations.

Transboundary transport of aluminum waste is subject to legislation based on the Basel Convention and OECD Rules.

15. Regulatory Information

The plate does not contain any material known to the State of California to cause cancer or adverse reproductive effects. However, trace amounts of material known to the State of California to cause cancer, such as acetaldehyde and formaldehyde, could be produced as thermal decomposition by-products during laser imaging. Under normal conditions of use the plate will not pose a physical hazard or health risk to employees.

Carcinogenicity Classification (components present at 0.1% or more):

CARCINOGENIC EFFECTS; MUTAGENIC EFFECTS; TERATOGENIC EFFECTS:

by ACGIH: NONE.

by IARC: NONE.

by OSHA: NONE

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372:

NONE.

16. Other Information

Validated by Kodak Polychrome Graphics on 2008-11-19.

Verified by Kodak Polychrome Graphics.
Printed 2008-11-19.

FOR INDUSTRIAL USE ONLY

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.